

Analogue Clocks

Series 0054

Impulse Slave Clocks – SR2

Features

- Attractive Modern Design
- Brushed Aluminium Case
- Dial Type A (1-12)
- Black Numerals and Hands
- White Dial Background
- Curved Glass Lens
- Surface Wall Mounting
- Individual Automatic Supervision
- Diameter 230 or 305 mm



Options

- Non-reflective Glass Lens
- Curved Acrylic Lens
- Dial Type B, C, J
- Double Sided Mounting
- Ceiling or Wall Suspension
- Weatherproof Enclosure
- Diameter 460, 610mm

Part Numbers

0054-32AC	230mm	2 Wire Minute Impulse SR2
0054-42AC	305mm	2 Wire Minute Impulse SR2
0054-75AC	460mm	2 Wire Minute Impulse SR2
0054-85AC	610mm	2 Wire Minute Impulse SR2

Description

Simplex Minute Impulse Self-Regulating Secondary Clocks are individually checked for agreement with the Simplex Time Control Centre (TCC) once each hour, providing uniform and accurate time. Any clock not in synchronization with the TCC will be automatically advanced or retarded as required. All clocks are connected to a 2 wire parallel circuit, 24VDC is the normal voltage. Each minute the TCC emits an electrical impulse, which is fed to each clock advancing it one minute. Each hour, rapid impulses are transmitted from the TCC to provide automatic hourly correction of slow clocks. With the 2 wire circuit polarity reversal is used for the rapid impulses. The recommended installation uses a Clipsal 408/3A three pin plug base (by others) to receive the Clipsal 409/3A fitted to the clock. The correction range of minute impulse-type clocks is 10 minutes fast and 15 minutes slow.

Power Requirements

24VDC, .034 AMP.

Contact Us

TIMETEK SYSTEMS
1300 669 630
sales@timetek.com.au